



NOW AVAILABLE WITH



## ***Faster, Smarter, More Efficient Moisture Analysis***

Moisture affects everything we use on a daily basis therefore in many cases it is important to be able to accurately determine the moisture content of samples. Equipped to handle routine and sophisticated measurements, our flagship MB120 moisture analyzer makes the whole process faster, easier, and more efficient. The MB120 allows you to analyze more samples, access saved data, and spend less time prepping and more time putting your results to work.

### ***Standard Features:***

- Get started quickly with SmartGuide™. This revolutionary feature automatically analyzes a sample and creates a method, thereby removing the guesswork from the initial setup.
- The MB120 has the capability to produce fast and accurate results due to features such as a halogen heating system, customizable shut-off criteria and four built-in drying profiles.
- The MB120's allows storage of up to 100 methods and 1,000 measurement results. Stored results can be exported and methods can be shared across multiple devices.

# MB120 Moisture Analyzer

## Simple and Powerful Moisture Analysis

- **SmartGuide™**

SmartGuide™ automatically analyzes a sample and creates a method, simplifying the method creation process and removes the guesswork from the initial setup.

- **Fast and Efficient Halogen Heating Technology**

Halogen heating dries samples efficiently and in a fraction of the time versus a traditional loss on drying measurement with an oven. The MB120 has a full operating temperature range of 40–230 °C, settable in 1-degree increments.

- **Uniform Drying for Precise, Repeatable Results**

The reflective sample chamber ensures uniform heating of each sample to yield reliable results of 0.01 % readability.

- **Four Drying Profiles**

Customize heating of specific samples with various drying programs; Standard, Fast, Ramp, and Step.

**Fast:** Quickest possible time to temperature

**Standard:** Minimal overshoot while achieving temperatures quickly

**Ramp:** Controlled ramping to temperatures



**Step:** Set three temperatures at three time intervals

- **Flexible and Configurable Shut-Off Criteria**

Customize your own test endpoint criteria to automatically end the test once moisture loss is no longer detected. Choose one of the built-in standard criterion or define your own.

| Default            |        |        |            |
|--------------------|--------|--------|------------|
| 23.08.2019 - 17:13 | 3.08   | %MC    | ▲          |
| 23.08.2019 - 17:02 | 3.13   | %MC    |            |
| ▼                  |        |        |            |
| Back               | Delete | Export | Statistics |

NOW AVAILABLE WITH



| Switch-off criterion |                  |
|----------------------|------------------|
| A30 (1 mg / 30 s)    | ▲                |
| A60 (1 mg / 60 s)    |                  |
| A90 (1 mg / 90 s)    |                  |
| Free (mg / s)...     | 1 mg / 120 s     |
| Free (% / s)...      | 1.00 % / 120 s ▼ |
| Back                 |                  |

**Method library**

|                    |        |                    |                   |
|--------------------|--------|--------------------|-------------------|
| Current method     | OHAUS  | Drying program     | Standard          |
| Drying temperature | 105 °C | Switch-off crit... | A60 (1 mg / 60 s) |

\* -- °C

0.000 g

Place sample pan and tare

Administrator 22.08.2019 - 16:51

# MB120 Moisture Analyzer





## Advanced Functionality

- **Internal Method Library**  
Store methods for up to 100 different samples - methods can be easily recalled and transferred to other units for quick setup.
- **Internal Result Storage**  
The MB120 will store 1000 results which can be printed or exported via USB memory stick as a group or individually for further analysis.
- **User Management**  
With User Management, MB120 provides operational control and aids compliance by restricting access so that unauthorized users may use the device but not change settings.
- **RS232 and USB Ports**  
Quick connections to a printer, PC or flash drive.

## Easy to Use and Maintain

- **Graphic Display with Touchscreen**  
Navigate the device easily with an intuitive user interface on a bright, color, and easy-to-read graphic display
- **Icon-Driven Menu Navigation**  
Easy to follow — no training required
- **4 Mechanical Keys for Fast One-Step Operation**  
Tare, Start/Stop, Print, On/Off
- **Easy Tool-Free Cleaning**  
Stainless steel surfaces are resistant to corrosion and wipe down quickly. Heating chamber components can be easily removed for easy cleaning - no tools required.



# MB120 Moisture Analyzer

| Model                       | MB120                                                                                            |
|-----------------------------|--------------------------------------------------------------------------------------------------|
| Capacity                    | 120 g                                                                                            |
| Readability                 | 0.01 % / 0.001 g                                                                                 |
| Moisture Range              | 0.01 % to 100 %<br>(0.01 % to 1000 % for regain mode)                                            |
| Output                      | RS232, USB Host, USB Device                                                                      |
| Heating Element             | Halogen                                                                                          |
| Temperature Range           | 40 – 230 °C (1 °C Increments)                                                                    |
| Power                       | 120 VAC                                                                                          |
| Operating Temperature Range | 50 – 104 °F / 10 – 40 °C                                                                         |
| Display Type                | 4.3 in/109 mm, QVGA, TFT touch screen                                                            |
| Display Results             | %moisture, %solids, %regain, time, temperature, weight, method name, drying curve and statistics |
| Pan Size                    | 3.5 in / 90 mm                                                                                   |
| Dimensions (W × H × D)      | 8.3 × 7.7 × 14.0 in / 211 × 180 × 355 mm                                                         |
| Net Weight                  | 11.5 lb / 5.23 kg                                                                                |
| Shipping Weight             | 18.4 lb / 8.35 kg                                                                                |

## Compliance

- **Product Safety:** IEC/EN 61010-1; IEC/EN 61010-2-010; CAN/CSA C22.2 61010-1; CAN/CSA C22.2 61010-2-010; UL 61010-1
- **Electromagnetic Compatibility:** IEC/EN 61326-1 Class B, Basic environments; FCC Part 15 Class A; Canada ICES-003 Class A
- **Compliance Marks:** CSA; CE; RCM; WEEE


## Additional Features

ABS top housing, stainless steel pan support, stainless steel metal pan handler, in-use cover, Seven shut-off criteria (manual shut-off with pre-set time, timed, autofree %/s, autofree mg/s, A30, A60 and A90), Four heating profiles (standard, fast, ramp and step), user guide, 14 operational languages (display only, no key in)

## Accessories

|                                    |          |
|------------------------------------|----------|
| Pan Handler .....                  | 30246947 |
| In-Use Cover .....                 | 30284478 |
| Scoop .....                        | 30284477 |
| Temperature Calibration Kit .....  | 11113857 |
| Anti-Theft Device .....            | 80850043 |
| Aluminum Pan (80) .....            | 80850086 |
| Glass Fiber Pads (200) .....       | 80850087 |
| Cage, Sample .....                 | 80252477 |
| Reusable Pan (3), 7 mm High .....  | 80252478 |
| Reusable Pan (3), 14 mm High ..... | 80252479 |
| SF40A Impact Printer .....         | 30064203 |

## Outline Dimensions



### OHAUS CORPORATION

7 Campus Drive  
Suite 310  
Parsippany, NJ 07054 USA

Tel: 800.672.7722

973.377.9000

Fax: 973.944.7177

[www.ohaus.com](http://www.ohaus.com)

*The management system  
governing the manufacture  
of this product is  
ISO 9001:2015 certified.*



80774987\_E 20200226 © Copyright OHAUS Corporation